

# Optional Features



## Tire Shiner

Tire dressing is the single most popular and requested extra service at a carwash.



## Water Reclaim System

Odor free reclaim water can help reduce utility bills, meet local regulations and is environmentally responsible.



## Entry Stations

The i5 is designed to work with nearly every major entrance station on the market today.



## Total Body Protection Arch

Introduce the fastest growing extra service on the market today at your wash. Compatible with most total body protectant products and a must-have for total customer satisfaction and added revenues.



## Onboard Wheel Blaster w/CTA

Completely covers tires with cleaning solution online. Includes mixing tank, pump, hydrominder, applicator trees, and solenoid valves.



## Bison Brush

Clean tires and rims better while reducing operating costs with SONNY'S new Bison Brush. Alternating staggered bristle lengths improve contact time while reaching deeper into rims for maximum cleaning.



## Spot Free and Water Softeners

Some areas have water quality that may warrant a softening system or water purifier.



## Free Standing Dryers

The i5 includes an industry leading 45hp onboard drying system that delivers fast results. A Free standing dryer option is available for even greater throughput.



**Bug Cleaner Applicator** This add-on has become very popular in rural markets or locations near highways as seasonal insect populations rise.



**High Pressure Option** Powerful high pressure manifolds that will complement the cleaning action of your i5.

## i5 Technical Data

Machine Height	117in	3302mm
Machine Width	12ft 8in	3861mm
Machine Depth	6ft 6in	1981mm
Vehicle Clearance Height	7ft 4in	2235mm
Vehicle Clearance Width	9ft 6in	2896mm
Distance Between Tracks	10ft 6in	3200mm
Recommended Bay Height	11ft	3353mm
Recommended Bay Width	15ft	4572mm
Recommended Bay Length	40ft	12192mm
Carwash Travel Speeds	20ft/min	6096mm/min
Average Wash Times	Quick Wash and Dry	2 min 30 sec
	Standard Wash & Dry	4 min 20 sec

# i5 SPECS

Water Supply Pipe	1in	
Water Pressure	40GPM @ 60PSI	151 lpm @ 4.2 bar
Water Consumption / Vehicle	42 gallons	159 l
Air Supply Pipe	½in	
Air Pressure	120PSI	8.3 bar
Power Supply	208V/230V/460VAC	3 Phase
	115VAC	1 Phase
Control Voltage	24 VDC	
Dryer Capacity	3 x 15HP or 3 x 10HP	
Connected Load	100 Amps (add 50 Amps for dryer)	